

CLOCKAUDIO

PP-2
48 VOLT D.C.
PHANTOM
POWER SUPPLY



Designed for use with condenser microphones.

PPA
PHANTOM
POWER ADAPTOR



9-48 Volt phantom power adaptor for electret condenser microphones.

CLOCKAUDIO

SPECIFICATIONS

- 2 Channel - XLR microphone inputs/outputs
- 48 volt d.c. output
- 20Hz - 20KHz bandwidth
- 600 Ohm fully balanced
- Lightweight
- 100/115/220/240 adjustable AC voltage selector
- LED power on/off indicator

DIMENSIONS	180mm x 145mm x 50mm
------------	----------------------

PACKING	245mm x 225mm x 90mm
---------	----------------------

NETT/SHIPPING WEIGHT	1.1 kilos/1.5 kilos
----------------------	---------------------

- Fitted with 3 pin male QG miniature connector and supplied with female cord plug
- Switchable bass cut filter - 4 dB per octave at 400 Hz to - 6 dB per octave at 100 Hz
- Switchable pad - 10 dB
- Fully balanced output
- Surface mount technology
- Robust all metal construction
- Finished in satin black

DIMENSIONS	19mm dia. 92mm overall length
------------	-------------------------------

PACKING	110mm x 80mm x 42mm
---------	---------------------

NETT/SHIPPING WEIGHT	94/117 grms
----------------------	-------------

CLOCKAUDIO®

Clockaudio Ltd - Headquarters

22 Arside Road, Waterlooville, Hampshire PO7 7UR, UK
Tel +44 (0)23 9225 1193 • Fax +44 (0)23 9225 1201
e-mail sales@clockaudio.co.uk

Clockaudio North America Inc.

2891 du Meunier, Unit 103, Vaudreuil-Dorion, Quebec J7V 8P2, Canada
Tel: (450) 424-9797 • Fax: (450) 424-3660
e-mail: info@clockaudio.com

www.clockaudio.com

As part of a continuous product improvement programme, we reserve the right to alter specifications without prior notice.

PP-2
48 VOLT D.C.
PHANTOM
POWER SUPPLY

PPA
PHANTOM
POWER ADAPTOR

PROFESSIONAL
MICROPHONE
SYSTEMS