

CLOCKAUDIO®

H-500 MONITOR
HEADPHONE



- Wide frequency response
- Closed diffused studio headphone
- Enhanced bass response
- 50mm Neodymium magnet drive units
- High SPL capability
- Excellent isolation from ambient noise
- Soft inner headband
- Detachable cable

H-500 MONITOR HEADPHONE

SPECIFICATIONS

TYPE	Dynamic closed-back, circumaural
SENSITIVITY	96dB SPL \pm 3dB @ 1mw
FREQUENCY	15Hz - 22KHz
MAX INPUT POWER	500mw
IMPEDANCE	24 Ohms
TDH	<0.3%
CABLE	Plug-in single cable approx 3 metres (10ft)
CONNECTOR	Gold plated mini stereo jack
STEREO ADAPTOR	Gold plated mini jack to 1/4" screw-on-adaptor
SPECIAL FEATURE	Detachable cable
ACCESSORY	Protective carrying pouch
NET/SHIPPING WEIGHT	374g (13.2oz) 638g (22.5oz)

CLOCKAUDIO[®]

Clockaudio Ltd - Headquarters

22 Arside Road, Waterlooville, Hampshire PO7 7UP, UK
Tel +44 (0)23 9225 1193 • Fax +44 (0)23 9225 1201
e-mail sales@clockaudio.co.uk

Clockaudio North America Inc.

2891 du Meunier, Unit 103, Vaudreuil-Dorion, Quebec J7V 8P2, Canada
Tel: (450) 424-9797 • Fax: (450) 424-3660
e-mail: info@clockaudio.com

www.clockaudio.com

PROFESSIONAL
MICROPHONE
SYSTEMS