

**CLOCKAUDIO**

STANDS

SM 75

S I20 X

S I20 S



SM 75



S I20 S



S I20 X

## SPECIFICATIONS

### STANDS

SM 75

S 120 X

S 120 S

#### S120

Table Microphone Base fitted with M10 x 1 screw thread mounting hole

#### S120S

As above but fitted with Press to Talk or Latching Switch

#### S120X

Table Microphone Base fitted with XLR Connector

#### S120XS

As S120X but fitted with Press to Talk or Latching Switch

HEIGHT	S120 / S120S	32mm
	S120X / S120XS	57mm including XLR

BASE DIAMETER	120mm
---------------	-------

CAVITY	The base has a cavity that can be accessed from the bottom via a metal plate secured by three screws. The space available, approx 74mm x 22.5mm, would be suitable for mounting additional electronics.
--------	---

PACKING	155mm x 135mm x 68mm
---------	----------------------

NETT/SHIPPING WEIGHT	1.87/1.95 Kilos
----------------------	-----------------

#### SM 75

Microphone Shock Absorbing Base for permanent fixing above or below the surface. Supplied complete with Female XLR and conversion adaptor for 3/8" BSW or 10mm screw fittings.

HEIGHT	32mm
	64mm including XLR

BASE DIAMETER	75mm
---------------	------

PACKING	80mm x 110mm x 40mm
---------	---------------------

NETT/SHIPPING	530/560 gms
---------------	-------------

## CLOCKAUDIO®

#### Clockaudio Ltd - Headquarters

22 Arnside Road, Waterlooville, Hampshire PO7 7UR, UK  
Tel +44 (0)23 9225 1193 • Fax +44 (0)23 9225 1201  
e-mail [sales@clockaudio.co.uk](mailto:sales@clockaudio.co.uk)

#### Clockaudio North America Inc.

2891 du Meunier, Unit 103, Vaudreuil-Dorion, Quebec J7V 8P2, Canada  
Tel: (450) 424-9797 • Fax: (450) 424-3660  
e-mail: [info@clockaudio.com](mailto:info@clockaudio.com)

[www.clockaudio.com](http://www.clockaudio.com)